Art Unit: 2600

CLMPTO 09/15/04 JW

Amend Claims 1,13,20,30,

Cancel Claims 3,5,21,23,32,34,

 (Currently Amended) A method for the prediction and optimization of a communications system comprising:

inputting data from a plurality of channels of the communications system;

predicting a performance of at least one of the plurality of channels using a plurality of parameters to characterize the performance of the channel;

oreating at least one transfer function model of the at least one of the plurality of channels, wherein the at least one transfer function model is simulated using physical configuration information of the communications system without use of direct measurements serves the at least one of the physicity of channels; and

optimizing the parameters of at least one of the plurality of channels in order to improve a bit rate of the at least one of the plurality of channels in the communications system.

(Freviously Presented) The method claim 1 wherein predicting the performance of the at least one of the plurality of channels comprises:

inputting data from at least one channel of the communications system into a prediction module;

determining an impairment on the at least one channel; characterizing the at least one channel using the at least one transfer function model and

3. (Cancelled)

Art Unit: 2600

4. (Previously Presented) The method of claim 2 wherein the at least one transfer function model is simulated using a spectrum management system.

- 5. (Cancelled)
- 6. (Previously Presented) The method of claim 2 wherein the impairment is selected from the group consisting of: a cross-talk impairment, an AM radio interference, a temperature impairment, and any combination thereof.
- 7. (Previously Presented) The method of olaim 1 wherein optimizing the parameters comprises:
 - a) choosing a first parameter for the channel;
 - h) phoosing a second parameter for the channal;
- c) determining an optimisation criteria for the channel based upon the first parameter and the ascond parameter;
- d) repeating a) o) until the optimization criteria is optimized for the communications system.
- 8. (Previously Presented) The method of claim 1 wherein the communications system is a wireline communications system.
- Previously Presented) The method of claim 1 wherein the communications system is a wireless communications system.
- (Previously Presented) The method of claim 1 wherein the communications system is an optical communications system.

Art Unit: 2600

11. (Previously Presented) The method of claim I wherein the communications system is a cable communications system.

- (Previously Presented) The method of claim 1 wherein the communications system is
 DSL communications system.
- 13. (Currently Amended) A system for the prediction and optimization of a communications system comprising:

a prediction module, wherein the prediction module predicts the performance of at least one channel in the communications system by providing a characterization of at least one parameter that describes the channel, and wherein the prediction module creates at least one transfer function model of the at least one channel such that the at least one transfer function model is simulated using physical configuration information of the communications system without use of direct measurements excess the at least one channel; and

an optimization module, wherein the optimization module finds the optimizacharacterization for the chantel based on at least one design criteria.

仑

- 14. (Previously Presented) The system of claim 13 wherein the design criteria are selected from the group consisting of: a cost of deployment; a signal to noise ratio, a total revenue, a bit rate, and any combination thereof.
- (5. (Previously Presented) The system of claim 13 wherein the communications system is a wireline communications system.

Art Unit: 2600



- 17. (Previously Presented) The system of claim 13 wherein the communications system is an optical communications system.
- 18. (Previously Presented) The system of claim 13 wherein the communications system is a cable communications system.
- 19. (Previously Presented) The system of claim 13 wherein the communications system is a DSL communications system.
- 20. (Currently Amended) A method for the prediction of the performance of a communications system comprising:

inputting data from at least one channel of the communications system into a prediction module;

creating at least one fransfer function model of the at least one channel, wherein the at least one transfer function model is simulated using physical configuration information of the communications system without use of direct measurements across the at least one channel:

determining an impairment on the at least one channel;

observativing the at least one channel using the at least one transfer function model and the impairment.

21. (Cancelled)

Application/Control Number: 09/710,487 Page 6

Art Unit: 2600

23. (Carcelled)

24. (Previously Presented) The method of claim 20 wherein the impairment is selected from the group consisting of: a cross-talk impairment, an AM radio interference, a temperature impairment, and any combination thereof.

- 25. (Previously Presented) The method of claim 20 wherein the communications system is a wireline communications system.
- 26. (Previously Presented) The method of claim 20 wherein the communications system is a wireless communications system.
- 27. (Previously Presented) The method of claim 20 wherein the communications system is an optical communications system.
- 28. (Previously Presented) The method of claim 20 wherein the communications system is a cable communications system.
- 29. (Previously Presented) The method of claim 20 wherein the communications system is a DSL communications system.
- (Currently Amended) A method for the prediction and optimization of a communications system comprising:

Art Unit: 2600

inputting data from at least one channel of the communications system;

creating at least one transfer function model of the at least one channel, wherein the at least one transfer function model is simulated using physical configuration information of the communications system without use of direct measurements corose the at least one channel;

predicting a performance of at least one of the channels using at least one parameter to characterize the performance of the channel; and

optimizing the at least one parameter of at least one of the channels in order to improve a bit rate of the at least one of the channels in the communications system.

31. (Previously Presented) The method claim 30 wherein predicting the performance of the at least one of the channels comprises:

inputting data from at least one channel of the communications system into a prediction module;

determining an impairment on the at least one channel;

characterizing the at least one charmel using the at least one transfer function model and the impairment.

- 32. (Cancelled)
- 33. (Previously Presented) The method of claim 31 wherein the at least one transfer

function model is simulated using a spectrum management system.

34. (Cancelled)

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

□ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.